



## ACCESSORY PRODUCTS

CARATTERISTICHE GENERALI - GENERAL FEATURES



### MX.V VELOCI FAST

- **MOTORE MONOFASE/TRIFASE, IP65, 0,12 kW - 4 POLI** (altre potenze disponibili su richiesta)
- **ALBERO IN PVC / AISI316L, LUNGHEZZE 600, 800, 900, 1100 mm** (altre lunghezze disponibili su richiesta)
- **ELICA IN PVC / AISI316L, 2 PALE, DIAMETRO 90 mm** (altri diametri disponibili su richiesta)
- **SINGLEPHASE/THREEPHASE MOTOR, IP65, 0,12kW-4 POLES** (other power supplies available upon request)
- **PVC/SS316L SHAFT, LENGTH 600, 800, 900, 1100 mm** (other lengths available upon request)
- **PVC/SS316L PROPELLER, 2 BLADES, DIAMETER 90 mm** (other lengths diameters upon request)



### MX.L LENTI SLOW

- **MOTORE+RIDUTTORE MONOFASE/TRIFASE, IP65, 0,12 kW - 4 POLI** (altre potenze disponibili su richiesta), **RAPPORTO DI RIDUZIONE 1:7-200 rpm (Standard), 1:20-70 rpm (Optional)**
- **ALBERO IN PVC / AISI316L, LUNGHEZZE 600, 800, 900, 1100 mm** (altre lunghezze disponibili su richiesta)
- **ELICA IN PVC / AISI316L, 2, 3, 6 PALE (piane o forate), DIAMETRO 90, 150, 220 mm** (altri diametri disponibili su richiesta)
- **SINGLEPHASE / THREEPHASE MOTOR + REDUCER, IP65, 0,12kW-4 POLES** (other power supplies available upon request), **REDUCER RATIO 1:7-200 rpm (Standard), 1:20-70 rpm (Optional)**
- **PVC/SS316L SHAFT, LENGTH 600, 800, 900, 1100 mm** (other lengths available upon request)
- **PVC/SS316L PROPELLER, 2, 3, 6 BLADES (flat or with holes), DIAMETER 90, 150, 220 mm** (other lengths diameters upon request)

